

Datasheet Flexible Recessed Cap



Release date : 10-06-2013
Revision date : 18-10-2017

Elskensakker 8, NL-5571 SK
Bergeijk, The Netherlands

Tel +31 497 542527
Fax +31 497 555399
Email info@dhatec.nl
Web www.dhatec.nl

General information

The Flexible Recessed Cap is suitable for hook lifting and closes the pipe against the elements. This protects the internal pipe surface.

Application

The Flexible Recessed Cap is placed over the pipe end and clamps itself to the outer pipe surface.

Features

- ✓ Fast and easy fitting and removal
- ✓ High resistance against tearing
- ✓ Suitable for hook lifting

Material specifications

Material : Low Density Polyethylene (LDPE)
Hardness : 40° shore D
Elasticity at break : 600 %
Tension at break : 21 Mpa
Modulus of elasticity : 60 Mpa
Material thickness : approx. 2mm (0.08")

Product range : On request
Product code : FRCY

Commodity / HS code : 39235090

Additional information

- Application temperature: -40°C / 60°C (-40°F / 140°F)
- Vent-hole is optional
- Breathable membrane is optional
- UV-resistance: For outdoor use: 0,5-2 years
- Application time: 1 – 2 minutes per pipe end
- Available in a wide range of standard and non-standard sizes



Fig.1 Flexible Recessed Cap



Fig.2 Pipe with Flexible Recessed Cap



Fig.3 Pipe with Flexible Recessed Cap