

# Datasheet PVC Plug with steel Bevel Protector



Release date : 23-05-2013  
Revision date : 18-10-2017

Elskensakker 8, NL-5571 SK  
Bergeijk, The Netherlands

Tel +31 497 542527  
Fax +31 497 555399  
Email [info@dhatec.nl](mailto:info@dhatec.nl)  
Web [www.dhatec.nl](http://www.dhatec.nl)

## **General information**

The PVC Plug is used in combination with the Dhatec Steel Bevel Protector to provide pipe end protection and pipe closure at the same time. The PVC Plug closed the pipe against the elements. This protects the internal pipe surface.

## **Application**

The PVC Pipe Cap is clamped inside the pipe with the steel Bevel Protector. The Clamping Clip will expand and the Bevel Protector forces itself strongly against the ID of the pipe.

## **Features**

- ✓ Bevel protection and pipe closure at the same time
- ✓ Suitable for long term pipe storage in all weather conditions
- ✓ Available in a wide range of standard and non-standard sizes
- ✓ Suitable for hook lifting

## **Material specifications**

Material : PVC  
Tensile strength wrap : 2.500 N/5cm\*  
Tensile strength weft : 1.800 N/5cm\*  
Tear resistance warp and weft : 250 daN\*\*  
Weight : 570 gr/m<sup>2</sup> (1.3lbs / 10.8ft<sup>2</sup>)  
Application temperature : -30°C / 70°C (-22°F / 158°F)

Product range : 203mm – 3.048mm (8" – 120")  
Product code : PLVC

Commodity / HS code : 39204390

## **Additional information**

- UV-resistance: Suitable for long term outdoor use
- Application time: 1-2 minutes per pipe end



*Fig.1 PVC Plug with steel Bevel Protector*



*Fig.2 PVC Plug with steel Bevel Protector in pipe*