Datasheet Reusable Bevel Protector

Release date : 10-06-2013 Revision date : 05-12-2016

Product range : 200mm – 3.048mm (8" - 120")

Product code : BR

Commodity / HS code : 73269098

DHATEC A SHAWCOR COMPANY

Elskensakker 8, NL-5571 SK Bergeijk, The Netherlands

Tel +31 497 542527 Fax +31 497 555399 Email info@dhatec.nl Web www.dhatec.nl

Application:

The Reusable Bevel Protector provides the best protection during pipe transport, storage and handling of pipes. The rounded buffer zone absorbs impact forces, leaving the bevel free of damage. The strong clamping system is designed to withstand transport vibrations and all handling procedures. With a new Clamping Clip, the same Bevel Protector can be reused.

Reasons to buy this product:

- 1. Fast and easy fitting and removal
- 2. Strong clamping
- 3. Suitable for hook lifting
- 4. Fitting on stacked pipes
- 5. Protection of the full circumference
- 6. Absorbance of large pipe tolerances

Use in process:

The two ends of the Bevel Protector are brought together and the Bevel Protector is positioned in the pipe-end by one simple push. A separate Clamping Clip is positioned between the two lips. By hammering on the Clamping Clip, the clip will expand and the Bevel Protector forces itself strongly against the ID of the pipe.

Material specifications:

Steel : DD 11 (Material number: 1.0332) Zinc plated steel : DX51D+Z275-M-A-C (Material number: 1.0226) Stainless steel : ANSI 304 (Material number: 1.4301)

Additional information:

- The Reusable Bevel Protector can be supplied with shockabsorbing profile or with a 85°-angle
- Absorbance of large pipe tolerances: Ø +2,0mm / -2,0mm (0.08" / -0.08")
- Clamping Clips of different lengths are available for covering even larger pipe tolerances or differences in wall thickness
- Processing tools available for easy application:
 Third Hand Tool and the Clamping Tool for Bevel Protector (ask for details)



Fig. 1 Reusable Bevel Protector with Clamping Clip



Fig. 2 Reusable Bevel Protector with Clamping Clip




Fig. 3 Bevel with Reusable Bevel Protector